

Item No.	DSJD-10	DSJD-20	DSJD-30	AS01-50
Power	10 W	20W	30W	50W
Luminous flux	1500 LM	2400 LM	3600LM	5800LM
Poly crystalline solar panel	6V 8W	6V 12W	6V 15W	6V 15W
Lithium battery	3.7V 8000mA	3.7V 10000mA	3.7V 12000mA	3.7V 14000mA
Charge Time	5H	5H	5H	5H
Lighting Time	16H	16H	16H	16H
Solar Panel Size(MM)	350*235*17	370*305*17	420*370*17	420*370*17
Lighting area	40m2	60m2	80m2	100m2
Installation height	3M-4M	3M-5M	4M-6M	6M-8M
Installation distance	9M-12M	9M-15M	12M-18M	18M-24M
Light efficiency	150LM/W	120LM/W	120LM/W	120LM/W
Light source	SMD5730			
Material	High quality die-casting aluminum alloy			
Light degradation rate	25000h ≤ 20 %			
Color rendering index	Ra ≥ 80			
Power factor	PF ≥ 0.96			
Rated life	≥ 50000hours			
Color temperature	3000K-7000K			
Working temperature	- 30 ~+ 5 0° C			
Input Volt age	DC12/24V			
Beam angle	60 °* 12 0 °			
IP code	IP 65 waterproof & dustproof			
Brand	YANGFA & Customized			
Warranty	2 years warranty			
Certificate	CE, RoHS, SAA, EMC,MSDS			
Application	garden , courtyard , road , parking lot, out door, etc.			
Available color	Silvery white/ customized			